



Virgo

Multi-Fit Downlight
Recess Cut-Out Adjustable Downlight



Technical

• Input Voltage	AC 200-240V
• Beam Spread	110°
• Power Factor	>0.85
• Operating Temp.	-20 to +40°C
• Materials	Polycarbonate
• IP Rating	IP44
• Dimmable	On Request
• Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
• Cut Out	80mm to 160mm 120mm to 200mm 50mm to 270mm
• Emergency Output	275Lm

Adjustable Bar For Multiple Cut-Outs

Virgo Features



TP(a)
Fire Rating



Adjustable
Cut-Outs



Wattage
Switchable



Tri- Colour
(3000K/4000K/6000K)



3 Pin Push Connector
As Standard

Note: The Virgo range uses fixed integral drivers and is therefore unable to support dimmable or emergency options.

Virgo					
Part Code	Size	Power	Efficacy	Output	Kelvin
VGO-PRO-WS-80/160TC	180mm	7W	110Lm/cW	770Lm	Tri-Colour: 3000K, 4000K & 6000K
		9W	110Lm/cW	990Lm	
		12W	110Lm/cW	1320Lm	
VGO-PRO-WS-120/200TC	220mm	10W	110Lm/cW	1100Lm	
		14W	110Lm/cW	1540Lm	
		18W	110Lm/cW	1980Lm	
VGO-PRO-WS-150/270TC	300mm	15W	110Lm/cW	1540Lm	
		20W	110Lm/cW	2200Lm	
		25W	110Lm/cW	2750Lm	

Net Weight	Diameter (A)	Height (B)	Cut Out
0.4kg	Ø180mm	20.5mm	80 to 160mm
0.53kg	Ø220mm	21.5mm	120 to 200mm
0.95kg	Ø300mm	25mm	150 to 270mm

Option	Option Code
3 Hour Emergency (Remote)	+ /EM
Dimming Options	See Below - Contact Office



SILVAIR CASAMBI


Accessories

Black or chrome trims available
(See codes below)




Accessory	Description
VGO-180-BLACK	Black Trim for 180mm Virgo
VGO-180-CHROME	Chrome Trim for 180mm Virgo
VGO-220-BLACK	Black Trim for 220mm Virgo
VGO-220-CHROME	Chrome Trim for 220mm Virgo
VGO-300-BLACK	Black Trim for 300mm Virgo
VGO-300-CHROME	Chrome Trim for 300mm Virgo

Dimensions



Photometric Data



Energy Efficiency Rating

