



ON-X



Backlit Panel - Tri-Colour - 4000K - 6000K
1195mmx295mm

Technical

• Input Voltage	AC 200-240V
• Diffuser Type	Opal
• Beam Spread	110°
• CRI	>80
• Power Factor	>0.95
• Typical UGR	<19
• Materials	Aluminium
• Operating Temp.	-20 to +50°C
• IP Rating	IP40
• Fire Rating	TP(a)
• Dimmable	On Request
• Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
• Emergency Output	300Lm



ON-X Features



ON-X Fixed Colour Temperature

Part Code	Power	Efficacy	Output	Kelvin
OX-TPA-WS2-12X3NW	20W	120Lm/cW	2400Lm	4000K
	26W	120Lm/cW	3120Lm	
	30W	120Lm/cW	3600Lm	
OX-TPA-WS2-12X3CW	20W	120Lm/cW	2400Lm	6000K
	26W	120Lm/cW	3120Lm	
	30W	120Lm/cW	3600Lm	

ON-X Tri-Colour Switchable

Part Code	Power	Efficacy	Output	Kelvin
OX-TPA-WS2-12X3TC	20W	120Lm/cW	2400Lm	Tri-Colour: 3000K, 4000K & 5000K
	26W	120Lm/cW	3120Lm	
	30W	120Lm/cW	3600Lm	

ON-X Tri-Colour Low Glare

Part Code	Power	Efficacy	Output	Kelvin
OX-TPA-WS2-12X3TC/LG	20W	120Lm/cW	2400Lm	Tri-Colour: 3000K, 4000K & 5000K
	26W	120Lm/cW	3120Lm	
	30W	120Lm/cW	3600Lm	


Net Weight | 1.7kg

Option	Option Code
3 Hour Emergency	+ /EM
Dimming Options	See Below - Contact Office




SILVAIR CASAMBI

Dimensions



Photometric Data



Energy Efficiency Rating