



ON-XLG

Backlit Panel - Tri-Colour - 4000K
1195mmx595mm



Technical

• Input Voltage	AC 200-240V
• Diffuser Type	Microprismatic
• Beam Spread	90°
• CRI	>80
• Power Factor	>0.95
• Typical UGR	<19
• Materials	Aluminium
• Operating Temp.	-20 to +50°C
• IP Rating	IP40
• Fire Rating	TP(a)
• Dimmable	On Request
• Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
• Emergency Output	300Lm

ON-X Features



IP40 Ingress Protection



TP(a) Fire Rating



Remote Emergency Option



Aluminium Housing



3 Pin Push Connector As Standard

ON-X Backlit Panel

Part Code	Power	Efficacy	Output	Kelvin
OX-TPA-WS2-12X6NW/LG	40W	120Lm/cW	3120Lm	4000K
	45W	120Lm/cW	3600Lm	
	50W	120Lm/cW	4560Lm	

Net Weight | 4kg

ON-X Tri-Colour Switchable


Part Code	Power	Efficacy	Output	Kelvin
OX-TPA-WS2-12X6TC/LG	40W	120Lm/cW	3120Lm	Tri-Colour: 3000K, 4000K & 5000K
	45W	120Lm/cW	3600Lm	
	50W	120Lm/cW	4560Lm	

Net Weight | 4kg

Option	Option Code
3 Hour Emergency	+ /EM
Dimming Options	See Below - Contact Office



Dimensions



Photometric Data

