



Halo

Decorative Circular Pendant

Technical

• Input Voltage	AC 100-240V
• CRI	80
• Beam Angle	106°
• Operating Temp.	-35 to +45°C
• Materials	Extruded Aluminium & Polycarbonate
• IP Rating	IP20
• Suspension Cable	2m AC Cable/Suspension
• Dimmable	DALI Dimmable
• Emergency Output	237Lm



Halo Spec



Internal Application



2m Cable



Aluminium Housing



White Available On Request

HALO


Part Code	ØSize (Outer)	ØSize (Inner)	Power	Efficacy	Output	Kelvin
HALOSPEC-38-600NW	660mm	540mm	38W	95Lm/cW	3610Lm	4000K
HALOSPEC-55-900NW	900mm	780mm	55W	95Lm/cW	5225Lm	4000K
HALOSPEC-75-1200NW	1200mm	1080mm	75W	95Lm/cW	7125Lm	4000K
HALOSPEC-94-1500NW	1500mm	1380mm	94W	95Lm/cW	8930Lm	4000K
HALOSPEC-126-2000NW	2060mm	1940mm	126W	95Lm/cW	11970Lm	4000K
HALOSPEC-151-2400NW	2460mm	2340mm	151W	95Lm/cW	14345Lm	4000K

Option	Option Code
3 Hour Emergency	+ /EM
Dimming Options	See Below - Contact Office
Indirect Option Available	Contact Office



SILVAIR CASAMBI

Dimensions - Outer Diameter



Direct/Indirect
& Tri-Colour
Options

Coming Soon

