



# Mitre Bolt

## Path Lighting Bulkhead (Plug & Play)

### Technical

• Input Voltage	AC 220-240V
• CRI	>80
• Power Factor	>0.92
• Operating Temp.	-40 to +70°C
• Materials	Polycarbonate
• IP Rating	IP65
• IK Rating	IK10
• Surge Protection	6Kv
• Dimmable	On Request
• Lifetime	50,000 hours, L90-B10 (Ta 25 °C)
• Emergency Output	350Lm



### Mitre Features



IP65 Ingress Protection



IK10 Impact Resistance



Wattage Switchable



Integral Photocell Sensor (Can Be Disabled)

### Mitre

Part Code	Power	Efficacy	Output	Kelvin
MITRE-BOLT-WS-TC	12W	140Lm/cW	1680Lm	Tri-Colour: 3000K, 4000K & 6000K
	17W	140Lm/cW	2380Lm	
	21W	140Lm/cW	2940Lm	
	24W	140Lm/cW	3360Lm	

Net Weight | 1.6kg

### Options

### Option Code

Dimmable Options

On Request

Dimensions - Please See Diagram Below

### Plug & Play Accessories

#### Emergency Kits

##### Part Code



LME-BOLT-MT-EMKIT/MT/ST

##### Description


Emergency Kit for MITRE BOLT



### Dimensions



### Photometric Data



### Energy Efficiency Rating

